

6847/11AGM-204-500

Navn: **Watchdog**
 Watchdog 220 MasterLINE, hvit
 Watchdog

Type: 6847/11AGM-204-500


EAN: 4011395150559

EI-nummer: 1471135

Beskrivelse: 230V, 16A, IP55 for påveggsmontasje. Dekningsområdet er 220°. Detektordelen kan vris nedover og fra side til side. Rekkevidde rett frem er 16m og 16m til siden, monteringshøyde 2,5m. Lysnivået kan reguleres fra 0,5–300 lux, tidsforsinkelse er 10sek – 30min.

Forpakning: 1/10

Enhet: STK



Teknisk spesifikasjon

Dimensjoner

Dimensjoner 115x125x141 mm

Vekt 550 g

Klassifisering

Kapslingsklasse IP55

Elektriske størrelser

Nominell effekt 3680 W/VA

Nominell nettspenning 230 V

Effektkoeffisient (cos φ) 0.6

Koblingsstrøm ≤ 16 AX

Elektronikk

Forsinkelsestid 10 s-30 min

Dekningsområde 220°, eteen 16 m, sivuille 16 m

Driftsfrekvens 50 ... 60 Hz

Farger

Farge Hvit

Driftstemperatur -25 ... 55 °C

ETIM

ETIM 7 EC000133 (EC000133)

ETIM 8 EC000133 (EC000133)

6847/11AGM-204-500

ETIM 8

Model	Movement sensor
With DALI interface	no
Constant light control	no
HVAC-control	no
Forced switch off	yes
Animal zone	no
Creep-under protection	yes
Networkable	no
Optimum mounting height	2.5 m
Staircase monitoring	yes
Bridging switch	no
Max. transmission range sideways	16 m
Max. transmission range frontally	16 m
Diameter detection range on floor	32 m
Suitable for wireless transmission	no
Remote operation	yes
With remote control	no
Response value sensitivity adjustable	yes
Response value luminosity adjustable	yes
With signal unit	no
Teach-function for response value luminosity	yes
Dim function with dimmer basic element	no
Mounting method	Surface mounted (plaster)
Material	Plastic
Material quality	Thermoplastic
Halogen free	yes
Surface protection	Untreated
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	no
Degree of protection (IP)	IP55
Frequency	50 ... 60 Hz
Nominal voltage	230 V
Min. switch-on time	10 s
Max. duty cycle	30 min

6847/11AGM-204-500

Detection angle horizontal	8 ... 220 °
Pivoting range sensor, horizontal	
Pivoting range sensor, vertical	
Response value luminosity	0.5 ... 1000 lx
Max. switching power	3680 W
Suitable for C-load	no
Temperature	-25 ... 55 °C
Max. starting current	80 A
Substation input	no
With alarm function	no