

6131/31-24-500

| | |
|--------------|--|
| Navn: | Tilstedeværelsesdetektor Tilstedeværelsesdetektor 360*, hvit, tak, premium KNX |
| Type: | 6131/31-24-500 |
| EAN: | 4011395185940 |
| EI-nummer: | 4544273 |
| Beskrivelse: | Tilstedeværelsesdetektor 360* premium m/integrert bustilkobler, 4 kanaler, RTC, hvac og konstantlysstyring regulering (dimming). Rekkevidde: høyde 2,5m: max 10,0m, høyde 3,0m: max 12,0m, høyde 4,0m: max 16,0m. |
| Forpakning: | 1 |
| Enhet: | STK |



ETIM

| | |
|--------|---------------------|
| ETIM 7 | EC001582 (EC001582) |
| ETIM 8 | EC001582 (EC001582) |

ETIM 8

| | |
|------------------------------|---------------------------|
| Bus system KNX | yes |
| Bus system KNX radio | no |
| Bus system radio frequent | no |
| Bus system LON | no |
| Bus system Powernet | no |
| Radio frequent bidirectional | no |
| Model | Presence detector |
| Mounting method | Surface mounted (plaster) |
| Material | Plastic |
| Material quality | Thermoplastic |
| Surface protection | Untreated |
| Surface finishing | Matt |
| Colour | White |
| RAL-number (similar) | 9016 |
| Transparent | no |
| With bus connection | no |
| Substation input | yes |
| Creep-under protection | yes |

6131/31-24-500

| | |
|--|----------|
| Operation mode switch | no |
| Animal zone | no |
| Staircase monitoring | yes |
| Response value luminosity adjustable | yes |
| Teach-function for response value luminosity | yes |
| Switch-off delay self-learning | no |
| Optimum mounting height | 3 m |
| Diameter detection range on floor | 12 m |
| Detection angle vertical | |
| Detection angle horizontal | |
| Number of channels | 4 |
| Min. switch-on time | 10 s |
| Max. duty cycle | 1092 min |